

Dulux TRADE

DULUX TRADE

POLYURETHANE VARNISH

Issued April 2007

607

PRODUCT INFORMATION

Typical Use	<p>Dulux Trade Polyurethane Varnish is a solvent-based interior varnish which gives a tough and durable finish. It can be used over bare wood and previously stained or varnished surfaces. It withstands knocks, scuffs and spills and is suitable for use on interior wood, veneer, cork and chipboard.</p> <p>Dulux Trade Polyurethane Varnish <u>is not</u> suitable for use on other surfaces such as masonry or outdoors.</p> <p>Before preparing any surface for painting, read the Safety, Health & Environmental information on page 2 about old lead-based paints.</p>
Pack Size	1, 2.5 and 5 Litre.
Colour Range	Clear Gloss, Satin or Matt and colours in satin finish only.
Composition (nominal)	<p>Pigment: Inert Matting Agents.</p> <p>Binder: Polyurethane Modified Alkyd.</p> <p>Solvent: Low Odour aliphatic hydrocarbon.</p>
Volume Solids	44% (nominal).
Thinning	<p>For sealing new or bare surfaces add up to 1 part of white spirit to 10 parts of varnish. For normal use thinning is not usually necessary.</p> <p>When sealing new or bare surfaces use thinned Dulux Trade Polyurethane Gloss Varnish only, as Matt or Satin may produce a cloudy finish.</p>
Application Method	Brush only. For Health and Safety reasons related to all solvent-based paints, spray application is not recommended.
Drying Times	<p><i>Single coat at standard thickness:</i></p> <p>Touch Dry: 6-8 hours.</p> <p>Recoat: 16-24 hours.</p>
Practical Coverage	On smooth surfaces of average porosity a litre of varnish is sufficient to apply one coat to an area of up to 16m ² .
Cleaning Up	<p>After use, remove as much varnish as possible from brushes before cleaning with white spirit.</p> <p>Do not use or store in extremes of temperature.</p>

SURFACE PREPARATION

Surfaces must be sound, clean and dry before treating.

Remove all loose and defective coatings, if necessary stripping back to bare wood.

Thoroughly rub down all surfaces in the direction of the grain to provide a 'key', using 'wet flattening' methods where possible, then wipe off with a damp, lint free cloth.

Seal all bare wood with a thinned coat of **Dulux Trade** Polyurethane Varnish - Gloss (see thinning above).

Fill any surface defects, open joints etc. Do not use linseed oil putty for making good with natural wood finishes.

In multi coat work, it is advisable to lightly rub down between coats, in the direction of the grain, using a suitable grade of abrasive paper and then wipe off with a damp, lint free cloth.

SYSTEM INFORMATION

Stir thoroughly before use.

After suitable preparation and sealing, in the case of bare wood, apply 1 or 2 coats of **Dulux Trade** Polyurethane Varnish.

SAFETY, HEALTH & ENVIRONMENTAL INFORMATION

SOLVENT-BASED VARNISH

FLAMMABLE.

Repeated exposure may cause skin dryness or cracking.

Contains cobalt carboxylate and ethyl methyl ketoxime. May produce an allergic reaction.

Keep away from sources of ignition. No smoking.

Contains white spirit. Use only in well ventilated areas. Ensure maximum ventilation during application and drying. When applying by brush or roller to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air fed respiratory protective equipment.

Avoid contact with skin and eyes. When applying it is advisable to wear eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleaner. Do not use solvent, thinners or white spirit.

Keep out of the reach of children. If swallowed, seek medical advice immediately and show this container or label. Do not use or store by hanging on a hook. Do not empty into drains or watercourses.

Before use refer to safety data sheet. This includes waste hazard categories.

Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact ICI Paints Technical Group, at ICI Paints, Wexham Road, Slough SL2 5DS.

Tel: 0870 242 1100 (national call rates apply)

EU limit value for this product (cat. : A/e) : 500 g/l (2007)

This product contains max. 485 g/l VOC

See www.duluxtrade.co.uk

VOC Content High 25% - 50%. VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

Dulux Trade and the ICI Roundel are Trademarks of ICI.

© ICI 07 (130407IT)

