

# Decking Oil

- Protects and enhances most types of timber decking
- Contains UV filters to prevent fading from sunlight
- Revives weathered and greying decking
- Suitable for use on fences, sheds and hot tubs



## USAGE

Exterior

## COVERAGE

1 Litre

8-10 m<sup>2</sup>

## APPLICATION

Brush or roller

## DRYING TIME

15 mins between coats, 24 hours final

## TOOL CLEANING

White Spirit

### Product use

Liberon Decking Oil is ideal for feeding, protecting and enhancing the natural beauty of most types of timber decking. It is perfect for reviving and restoring colour to old or new decking and is suitable for use on fences, garden sheds, gates and hot tubs etc. Containing UV filters it helps reduce discolouration and fading from the sun, whilst maintaining the finish.

### Preparation

Ensure the surface is clean, dry and free from previous finishes and dust. Lightly sand new wood and clean old wood with Liberon Decking Cleaner.

### Application

Stir well before use. Apply a generous coat of Decking Oil with a paint brush or roller. Allow to penetrate for 15 to 30 minutes then apply the second coat without waiting for the first to dry. Continue to apply more coats of Decking Oil until the timber no longer absorbs the oil. Wipe off any excess with a lint-free cotton cloth and allow to dry for 24 to 48 hours before using the decking.

**Important:** Oil finishes bring out the natural colours of timber. A wet surface will be an indication of the final colour. Always test product on a spare surface or inconspicuous area for colour, compatibility and end result.

### Cleaning and maintenance

For general maintenance clean with Liberon Decking Cleaner. We recommend applying 1 or 2 coats of Decking Oil once a year as routine maintenance. On high traffic areas re-apply 1 or 2 coats of Decking Oil as and when required.

### Precautions

- Wear suitable clothing and protective gloves when using the Decking Oil.
- Store Liberon Decking Oil at a temperature above 5°C. Always replace the lid otherwise the oil can deteriorate.
- Oily cloths can self combust. Do not leave impregnated cloths in bundles. Before discarding lay them flat outside to dry to avoid a fire hazard.
- May not be suitable for some foreign hardwoods.
- On exterior oak we recommend the use of Liberon Pure Tung Oil.

### Packaging

Decking Oil is available in 2.5 L and 5 L containers.

**Colours**

Teak and clear.

**Health and Safety**

Repeated exposure may cause skin dryness or cracking. Keep out of the reach of children. Do not empty into drains. Use only in well-ventilated areas. If swallowed do not induce vomiting: seek medical advice and show this container or label. Contains methylethylketoxime. May produce an allergic reaction.

**VOC information**

EU limit value for Decking Oil (CatA/I): 600 g/L (2007). Decking Oil contains Max 590 g/L VOC.

For further information on this or other Liberon products please contact Liberon Technical Services on 01797 361136.

This document was created with Win2PDF available at <http://www.daneprairie.com>.  
The unregistered version of Win2PDF is for evaluation or non-commercial use only.